

Carbon Monoxide

CO 3E 300

Product Data Sheet

CO 3E 300

FEATURES

Amperometric 3 electrode sensor cell
Very selective
Highly sensitive
Long lifetime

TYPICAL APPLICATIONS

TLV-monitoring, leakage detection
portable & fixed point applications
Oil & Petrochemical industry, parking garages, Mining, Steel Industry

PART NUMBER INFORMATION

MINI	0248-034-30009
4 series adaptation	0248-034-30049
7 series adaptation	0248-034-30079

The manufacturer deems the data contained herein as factual, and the opinions expressed are those of qualified experts based on the results of tests conducted. The above data can not be used as a warranty provision or representation for which the manufacturer assumes legal responsibility. The data are offered solely for consideration, investigation and verification. Any use of this information is subject to federal, state and local laws and regulations.

Product Data Sheet

CO 3E 300

TECHNICAL SPECIFICATIONS


Measuring Range	0-500 ppm
Sensitivity Range	70 nA/ppm \pm 20 nA/ppm
Zero Current at 20 °C	< 150 nA
Resolution at 20 °C	< 3 ppm
Bias Potential	0 mV
Linearity	< 5% full scale
Response Time at 20 °C	
t50	< 10 s calculated from 2 min. exposure time
t90	< 30 s calculated from 2 min. exposure time
Long Term Sensitivity Drift	< 10% per 6 months
Operation Conditions	
Temperature Range	-40 °C to + 50 °C
Humidity Range	15-90 % r.H., non-condensing
Effect of Humidity	no effect on base line shift, longer exposure to dry gas might decrease the sensitivity
Sensor Life Expectancy	> 4 years
Warranty	24 months

The manufacturer deems the data contained herein as factual, and the opinions expressed are those of qualified experts based on the results of tests conducted. The above data can not be used as a warranty provision or representation for which the manufacturer assumes legal responsibility. The data are offered solely for consideration, investigation and verification. Any use of this information is subject to federal, state and local laws and regulations.

Product Data Sheet

CO 3E 300

OUTPUT vs. TEMPERATURE:




The manufacturer deems the data contained herein as factual, and the opinions expressed are those of qualified experts based on the results of tests conducted. The above data can not be used as a warranty provision or representation for which the manufacturer assumes legal responsibility. The data are offered solely for consideration, investigation and verification. Any use of this information is subject to federal, state and local laws and regulations.

Product Data Sheet

CO 3E 300

ZERO READING vs. TEMPERATURE:



The manufacturer deems the data contained herein as factual, and the opinions expressed are those of qualified experts based on the results of tests conducted. The above data can not be used as a warranty provision or representation for which the manufacturer assumes legal responsibility. The data are offered solely for consideration, investigation and verification. Any use of this information is subject to federal, state and local laws and regulations.

Product Data Sheet

CO 3E 300

CROSS SENSITIVITIES AT 20°C

Gas	Concentration	Reading [ppm]
Acetic Acid	sat. vapor	0
Alcohols (i.e. IPA)	1025 ppm	0 ¹
Ammonia	100 ppm	0.1
Carbon Dioxide	10 %	0
Chlorine	1 ppm	0
Chlorine Dioxide	1 ppm	0
Gasoline Vapour	% range	0 ¹
Hydrogen	3000 ppm	1000
Hydrogen Sulfide	20 ppm	0 ¹
Nitric Oxide	100 ppm	25
Nitrogen Dioxide	10 ppm	0 ¹
Sulfur Dioxide	20 ppm	0 ¹

1) With inboard filter; to remove TLV levels of interfering gases; continuous high level exposure may reduce the efficiency of the filter material.

Notes:

1. Interference factors may differ from sensor to sensor and with life time. It is not advisable to calibrate with interference gases
2. This table does not claim to be complete. The sensor might also be sensitive to other gases.

The manufacturer deems the data contained herein as factual, and the opinions expressed are those of qualified experts based on the results of tests conducted. The above data can not be used as a warranty provision or representation for which the manufacturer assumes legal responsibility. The data are offered solely for consideration, investigation and verification. Any use of this information is subject to federal, state and local laws and regulations.

Product Data Sheet

Safety Note

This sensor is designed to be used in safety critical applications. To ensure that the sensor and/or instrument in which it is used, are operating properly, it is a requirement that the function of the device is confirmed by exposure to target gas (bump check) before each use of the sensor and/or instrument. Failure to carry out such tests may jeopardise the safety of people and property.

Attention

Use of this range of sensors requires complete understanding of the instructions. Before using this range, please carefully read 'Application Notes'.

For further assistance on sensor selection and use, please contact a member of the Technical Sales team.

The manufacturer deems the data contained herein as factual, and the opinions expressed are those of qualified experts based on the results of tests conducted. The above data can not be used as a warranty provision or representation for which the manufacturer assumes legal responsibility. The data are offered solely for consideration, investigation and verification. Any use of this information is subject to federal, state and local laws and regulations.