**Ammonia** 

NH3 3E 100

### NH3 3E 100

#### **FEATURES**

Amperometric 3 electrode sensor cell Fixed organic gel electrolyte No CO2 interference 0 volt bias operation

### **TYPICAL APPLICATIONS**

TLV-monitoring, leakage detection
Fixed point applications in cold storages & refrigeration plants only
For other applications please use NH3 3E SE versions
No background concentrations of ammonia & alcohols\*

#### PART NUMBER INFORMATION

MINI	1845-031-30009
4 series adaptation	1845-031-30049
7 series adaptation	1845-031-30079

#### Note:

- Background concentrations of ammonia and alcohols might shorten life time of sensor
- Exposure to high concentrations of alcohols can cause a high loss of sensor sensitivity

### NH3 3E 100

#### **TECHNICAL SPECIFICATIONS**

Measuring Range 0–100 ppm

Sensitivity Range 90 nA/ppm ± 40 nA/ppm

Zero Current at  $20 \,^{\circ}\text{C}$  <=  $\pm 150 \,\text{nA}$ Resolution at  $20 \,^{\circ}\text{C}$  <2 ppm Bias Potential  $0 \,^{\circ}\text{MV}$ 

Linearity <5% full scale

Response Time at 20 ℃

t50 <20 s calculated from 5 min. exposure time calculated from 5 min. exposure time

Long Term Sensitivity Drift <10% per 6 months

**Operation Conditions** 

Temperature Range -40 °C to +40 °C

Humidity Range 15–90% r.H, non–condensing

Effect of Humidity an abrupt change of r.H. will cause a short term drift of zero


reading

Sensor Life Expectancy > 18 months in air

Warranty 12 months


## NH3 3E 100

#### **OUTPUT vs. TEMPERATURE:**



## NH3 3E 100

#### **ZERO READING vs. TEMPERATURE:**



### **NH3 3E 100**

#### **CROSS SENSITIVITIES AT 20 ℃**

Gas	Concentration	Reading [ppm]
Alcohols	1000 ppm	yes / n.d.
Carbon Monoxide	100 ppm	40
Chlorine	1 ppm	-6
Nitrogen Dioxide	10 ppm	-15
Sulfur Dioxide	20 ppm	yes / n.d.
Hydrogen	10000 ppm	1000
Hydrogen Sulfide	20 ppm	25

#### Notes:

- 1. Interference factors may differ from sensor to sensor and with life time. It is not advisable to calibrate with interference gases if not otherwise stated
- 2. This table does not claim to be complete. The sensor might also be sensitive to other gases

### **Safety Note**

This sensor is designed to be used in safety critical applications. To ensure that the sensor and/or instrument in which it is used, are operating properly, it is a requirement that the function of the device is confirmed by exposure to target gas (bump check) before each use of the sensor and/or instrument. Failure to carry out such tests may jeopardise the safety of people and property.

### **Attention**

Use of this range of sensors requires complete understanding of the instructions. Before using the sensors, please carefully read 'Application Notes'.

For further assistance on sensor selection and use, please contact a member of the Technical Sales team.

The manufacturer deems the data contained herein as factual, and the opinions expressed are those of qualified experts based on the results of tests conducted. The above data can not be used as a warranty provision or representation for which the manufacturer assumes legal responsibility. The data are offered solely for

consideration, investigation and verification. Any use of this information is subject to federal, state and local laws and regulations.