

**Nitrogen Dioxide**

**NO<sub>2</sub> 3E 50**

# Product Data Sheet

## NO2 3E 50

### FEATURES

Amperometric 3 electrode sensor cell  
Good zero stability  
Fast response  
High resolution

### TYPICAL APPLICATIONS

TLV monitoring, parking garages

### PART NUMBER INFORMATION

MINI	2241-032-30009
4 series adaptation	2241-032-30049

The manufacturer deems the data contained herein as factual, and the opinions expressed are those of qualified experts based on the results of tests conducted. The above data can not be used as a warranty provision or representation for which the manufacturer assumes legal responsibility. The data are offered solely for consideration, investigation and verification. Any use of this information is subject to federal, state and local laws and regulations.

# Product Data Sheet

## NO2 3E 50

### TECHNICAL SPECIFICATIONS


Measuring Range	0–50 ppm
Sensitivity Range	200 nA/ppm $\pm$ 40 nA/ppm (negative signal)
Zero Current at 20 °C	< $\pm$ 20 nA
Resolution at 20 °C	< 0.1 ppm
Bias Potential	0 mV
Linearity	< 5% full scale
Response Time at 20 °C	
t50	< 10 s calculated from 4 min. exposure time
t90	< 30 s calculated from 4 min. exposure time
Long Term Sensitivity Drift	< 5% per month
Operation Conditions	
Temperature Range	-20 °C to +40 °C
Humidity Range	15–90% r.H, non–condensing
Effect of Humidity	an abrupt change of r.H. will cause a short term drift of zero reading
Sensor Life Expectancy	> 24 months in air
Warranty	12 months

The manufacturer deems the data contained herein as factual, and the opinions expressed are those of qualified experts based on the results of tests conducted. The above data can not be used as a warranty provision or representation for which the manufacturer assumes legal responsibility. The data are offered solely for consideration, investigation and verification. Any use of this information is subject to federal, state and local laws and regulations.

# Product Data Sheet

## NO2 3E 50

### OUTPUT vs. TEMPERATURE:




The manufacturer deems the data contained herein as factual, and the opinions expressed are those of qualified experts based on the results of tests conducted. The above data can not be used as a warranty provision or representation for which the manufacturer assumes legal responsibility. The data are offered solely for consideration, investigation and verification. Any use of this information is subject to federal, state and local laws and regulations.

# Product Data Sheet

## NO2 3E 50

### ZERO READING vs. TEMPERATURE:



The manufacturer deems the data contained herein as factual, and the opinions expressed are those of qualified experts based on the results of tests conducted. The above data can not be used as a warranty provision or representation for which the manufacturer assumes legal responsibility. The data are offered solely for consideration, investigation and verification. Any use of this information is subject to federal, state and local laws and regulations.

# Product Data Sheet

## NO2 3E 50

### CROSS SENSITIVITIES AT 20 °C

Gas	Concentration	Reading [ppm]
Alcohols	1000 ppm	0
Carbon Dioxide	5000 ppm	0
Chlorine	1 ppm	1
Nitric Oxide	100 ppm	0.4
Sulfur Dioxide	20 ppm	-5
Hydrogen	3000 ppm	0

Notes:

1. Interference factors may differ from sensor to sensor and with life time. It is not advisable to calibrate with interference gases.
2. This table does not claim to be complete. The sensor might also be sensitive to other gases.

The manufacturer deems the data contained herein as factual, and the opinions expressed are those of qualified experts based on the results of tests conducted. The above data can not be used as a warranty provision or representation for which the manufacturer assumes legal responsibility. The data are offered solely for consideration, investigation and verification. Any use of this information is subject to federal, state and local laws and regulations.

# Product Data Sheet

## Safety Note

This sensor is designed to be used in safety critical applications. To ensure that the sensor and/or instrument in which it is used, are operating properly, it is a requirement that the function of the device is confirmed by exposure to target gas (bump check) before each use of the sensor and/or instrument. Failure to carry out such tests may jeopardize the safety of people and property.

## Attention

Use of this range of sensors requires complete understanding of the instructions.

Before using this range of sensors please carefully read 'Application Notes'.

For further assistance on sensor selection and use, please contact a member of the Technical Sales team.

---

The manufacturer deems the data contained herein as factual, and the opinions expressed are those of qualified experts based on the results of tests conducted. The above data can not be used as a warranty provision or representation for which the manufacturer assumes legal responsibility. The data are offered solely for consideration, investigation and verification. Any use of this information is subject to federal, state and local laws and regulations.